## IN THE CLAIMS:

1. (Currently Amended) An assembling method of a capsule medical apparatus including a sealed capsule having a cylindrical casing with a central axis, an illuminating unit, an image pick-up unit for picking up an image of a portion illuminated by the illuminating unit, and an objective optical system arranged in an optical path of for focusing an image on the image pick-up unit through an optical path of the objective optical system, wherein the objective optical system is attached to a fixing frame, the assembling method comprising:

displaying an image area of the image pick-up unit and establishing one or more reference positions thereon in order to locate a center position of said image area;

displaying an image of the fixing frame and overlapping the image of the fixing frame with the image area of the image pick-up unit;

a positioning step of positioning a reference position of a the fixing frame of the objective optical system so that it matches a reference such that the center position of an the image area of the image pick-up unit coincides with the image pick-up unit center position of the image of the fixing frame, the optical path of the objective optical system, and the central axis of the cylindrical casing; and

a fixing step [[of,]] after the positioning step[[,]] wherein fixing the image pick-up unit and the fixing frame are attached and made to be fixed in position with respect to each otherso that a reference surface of the fixing frame comes into contact with a corresponding surface of the image pick-up unit.

2. (Withdrawn) A capsule medical apparatus comprising: an illuminating unit;

an image pick-up unit which picks up an image of a portion illuminated by the illuminating unit;

an objective optical system arranged along an optical path of the image pick-up unit;

a sealed capsule which seals and incorporates the illuminating unit, the image pick-up unit, and the objective optical system;

a fixing frame to which a first objective lens configuring an objective optical system is fixed, the fixing frame being fixed at a reference position of an image area of the image pick-up unit such that a reference position of the fixing frame matches the reference position of the image area;

a guiding frame extended in an optical path direction on a surface of the fixing frame on an opposite side not facing the image pick-up unit; and

a movable frame to which a second objective lens configuring an objective optical system is fixed, the movable frame being positioned and fixed in the optical path direction by being moved in the optical path direction relative to the guiding frame.

- 3. (Canceled)
- 4. (Previously Presented) An assembling method of a capsule medical apparatus according to Claim 1, wherein the reference position of the image area is on one of a corner portion around the image area and on at least a part of peripheral circuits of the image pick-up unit.
- 5. (Withdrawn) A capsule medical apparatus according to Claim 2, wherein the reference position of the image area is on one of a corner portion around the image area and on at least a part of peripheral circuits of the image pick-up unit.

- 6. (Currently Amended) An assembling method of a capsule medical apparatus according to Claim 1, wherein the fixing frame has a shape by which such that, when viewed along the optical path, after the fixing frame is arranged to oppose a surface of the image area of the positioned and fixed onto the image pick-up unit, such that the reference position of the fixing frame matches the reference position of the image area of the image pick-up unit, it is viewed along an optical path that at least a part of one of a corner portion around the image area and peripheral circuits of the image pick-up unit exists is outside the fixing frame.
- 7. (Withdrawn) A capsule medical apparatus according to Claim 2, wherein the fixing frame has a shape by which, when the fixing frame is arranged to oppose a surface of the image area of the image pick-up unit such that the reference position of the fixing frame matches the reference position of the image area of the image pick-up unit, it is viewed along an optical path that at least a part of one of a corner portion around the image area and peripheral circuits of the image pick-up unit exists outside the fixing frame.
- 8. (Previously Presented) An assembling method of a capsule medical apparatus according to Claim 1, wherein the fixing frame has a leg portion for fixing, which is extended to a part of a side surface having no connecting terminals and the fixing frame fixes the leg portion for fixing to a fixing substrate of the image pick-up unit.
- 9. (Withdrawn) A capsule medical apparatus according to Claim 2, wherein the fixing frame has a leg portion for fixing, which is extended to a part of a side surface having no connecting terminals and the fixing frame fixes the leg portion for fixing to a fixing substrate of the image pick-up unit.

apparatus according to Claim 1, wherein the objective optical system includes further comprising a first lens mounted to the fixing frame and covering the image pick-up unit, and a second lens for adjusting the focus of an image picked up by the image pick-up unit, the second lens being mounted to a movable frame that is interlocked with the fixing frame and movable, the method further comprising-movably interlocking the movable frame with the fixing frame such that an image picked up by the image pick-up unit is properly focused, and adjusting a distance of the first lens to the second lens along the optical path by moving the movable frame relative to the fixing frame, thereafter fixing the position of the movable frame with respect to the fixing frame, and accordingly fixing the position of the second lens with respect to the first lens.

positioning the movable frame in advancing and returning directions of the optical path by advancing or returning the movable frame to a guide portion in the direction of the optical path, the movable frame to which the second lens is fixed, the guide portion formed in the returning direction of the fixing frame and guiding the movable frame.

11. (Withdrawn) A capsule medical apparatus according to Claim 2, further comprising:

the objective optical system includes the first objective lens mounted to the fixing frame and a second objective lens mounted to the movable frame; and

positioning the movable frame in advancing and returning directions of the optical path by advancing or returning the movable frame to a guide portion in the direction of the optical path, the movable frame to which the second objective lens is fixed, the guide portion formed in the returning direction of the fixing frame and guiding the movable frame.

12. (Withdrawn) A capsule medical apparatus according to Claim 2, further comprising:

an electrical circuit block having an outer shape which is slightly smaller than an inner diameter of a capsule-shaped exterior, the capsule-shaped exterior having a plurality of electrical substrates with different functions, the electrical substrates being electrically conductive and being mechanically fixed via a connecting member in parallel with each other.

- 13. (Withdrawn) A capsule medical apparatus according to Claim 2, wherein an antenna for radio transmission is arranged in parallel with an optical axis of the objective optical system.
- 14. (Withdrawn) A capsule medical apparatus according to Claim 2, wherein the illuminating unit comprises a plurality of light emitting diodes, and a control operation is performed so that light emitting timings of the plurality of light emitting diodes are lit on intermittently at different timings within an exposure time of the image pick-up unit.
- 15. (Withdrawn) A capsule medical apparatus comprising an electric circuit block having an outer shape slightly smaller than the inner diameter of a capsule-shaped exterior, the capsule-shaped exterior having a plurality of electrical substrates with different functions, the electrical substrates being electrically conductive and being mechanically fixed via a connecting member in parallel with each other.
- 16. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein the connecting member comprises a plurality of pins which can be arranged at the same interval or at an interval larger than that between plurality of soldering balls or than the height of mounting parts of a plurality of substrates.

- 17. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein the connecting member is an MID (Molded Interconnect Devices) obtained by three-dimensionally forming thereon a plurality of connecting terminals or a lead frame formed integrally to a coupling portion which can easily be cut off after connection.
- 18. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein a pad, to which the connecting member of one electrical substrate is attached, is extended to the outer shape of the substrate.
- 19. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein a plurality of electrical substrates are overlapped and are fixed, and are soldered by flowing them to a flow furnace in a lump.
- 20. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein the electrical substrate has a fitting hole for fitting into the connecting member.
- 21. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein a battery for driving is arranged to the rear end side of the electrical circuit block and the capsule medical apparatus has a flexible substrate which electrically connects the battery and the electrical circuit block.
- 22. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein a connecting end comprises a plurality of soldering balls for electrically connecting the plurality of electrical substrates, and the inclination of the electric substrates can be prevented by connecting at least two sides of the plurality of electrical substrates.

- 23. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein the electrical substrates are substantially circular or substantially polygonal, and have substantially the same maximum outer shapes.
- 24. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein the electric circuit block has at least an image pick-up unit, a first electric substrate having a cave portion for fixing another electric part to the rear surface of the image pick-up unit, a second electric substrate having a cave portion for fixing a control portion for controlling at least the image pick-up unit, and a connecting terminal for connecting the first and second electric substrates.
- 25. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein two electric parts having different functions are layered and are mounted on one surface of at least one of the electric substrates.
- 26. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein an antenna for radio transmission is arranged substantially in parallel with the optical axis of the objective optical system.
- 27. (Withdrawn) A capsule medical apparatus according to Claim 15, wherein the illuminating unit comprises a plurality of light emitting diodes, light emitting timings of the plurality of light emitting diodes are controlled to be deviated within an exposure time of the image pick-up unit and to intermittently be lit on.
- 28. (Withdrawn) An assembling method of a capsule medical apparatus having a sealed capsule, the sealed capsule having an illuminating unit, an image pick-up unit

for picking up an image of a portion illuminated by the illuminating unit, and an objective optical system in front of the image pick-up unit, the assembling method comprising the step of:

connecting one electric substrate for fixing the image pick-up unit to another electric substrate having a function different from that thereof by using connecting terminals at an interval less than that between the connecting terminals while regulating the outer diameters of the electric substrates.

29. (Withdrawn) An assembling method of a capsule medical apparatus having a sealed capsule, the sealed capsule having an illuminating unit, an image pick-up unit for picking up an image of a portion illuminated by the illuminating unit, and an objective optical system in front of the image pick-up unit, the assembling method comprising the step of:

mounting the image pick-up unit on the sealed capsule so that when the center of an image pick-up sensor of the image pick-up unit is deviated from the center of an image area of the image pick-up sensor, the center of the image area is substantially in the center of an electric substrate for fixing the image pick-up sensor.

30. (Withdrawn) A capsule medical apparatus comprising: an illuminating unit;

an image pick-up unit for picking up an image of a portion illuminated by the illuminating portion;

an objective optical system in front of the image pick-up unit;
a transparent cover which is substantially hemispherical in front of the objective optical system; and

a sealed capsule which seals and incorporates, together with the transparent cover, the illuminating unit, the image pick-up unit, and the objective optical system,

wherein a positioning unit is formed for positioning operation by touching a substrate surface of the illuminating unit to an inner surface of the transparent cover so that the positioning unit is fixed to the circumferences of the illuminating unit and the objective optical system after adjusting optical axes of the objective optical system and the image pick-up unit to be in-focus, and so that the center of curvature of the transparent cover in front of the circumferences of the illuminating unit and the objective optical system, a pupil position of the objective optical system, and a light emitting position of the illuminating unit are fixed to a restricted position for preventing flares.

31. (Withdrawn) A medical method for examination, curing, and treatment in a body using a capsule medical apparatus, the capsule medical apparatus having:

an illuminating unit;

an image pick-up unit for picking up an image of a portion illuminated by the illuminated unit;

an objective optical system in front of the image pick-up unit; and
a sealed capsule which seals and incorporates the illuminating unit, the
image pick-up unit, and the objective optical system,

the medical method comprising the steps of:

forming the illuminating unit by a plurality of light emitting diodes; and controlling light emitting timings of the plurality of light emitting diodes so that they are deviated within an exposure time of the image pick-up unit and are intermittently lit on.

32. (Previously Presented) An assembling method of a capsule medical apparatus according to claim 1, wherein when the fixing frame is fixed to the image pick-up unit, a part of one of a corner portion around the image area not covered by the fixing frame and peripheral circuits of the image pick-up unit is exposed on a surface of the image area of the image pick-up unit to which the fixing frame is fixed.